
 <p><b>BSHD-100</b> <b>without Hard Disk</b></p>	存储媒体: 2.5英寸硬盘 (20G/30G/40G/60G/80G)	
	显 示: 外接电视机	
	输出接口: AV/VGA	
	视频播放: MPEG4: DIVX/AVI	
	MPEG2: MPG/VOB (DVD/SVCD)	
	MPEG1: MPG/DAT(VCD)	
	音频播放: MP3、WMA	
	图片浏览: JPEG	
	分 辨 率: >500TV Line	
	PC 连接: USB2.0	
	操作方式: 遥控器配合OSD菜单	
	视频制式: PAL/NTSC制式	
	电源电压: AC100-240V 50/60Hz	
	尺 寸: 131 (L) X80 (H) X 19 (D) mm	
重 量: 约215g		
 <p><b>BSHD-101</b> <b>without Hard Disk</b></p>	存储媒体: 2.5英寸硬盘 (20G/30G/40G/60G/80G)	
	显 示: 外接电视机或VGA显示器	
	方	
	输出接口: AV/VGA	
	视频播放: MPEG4: DIVX/AVI	
	MPEG2: MPG/VOB (DVD/SVCD)	
	MPEG1: MPG/DAT(VCD)	
	音频播放: MP3、WMA	
	图片浏览: JPEG	
	分 辨 率: >500TV Line	
	PC 连接: USB2.0	
	操作方式: 遥控器配合OSD菜单	
	视频制式: PAL/NTSC制式	
	电源要求: DC5.0V	
尺 寸: 131 (L) X80 (H) X 19 (D) mm		
重 量: 约215g		



**BSHD-102**  
without Hard Disk

存储媒体: 2.5英寸硬盘 (20G/30G/40G/60G/80G)
显示: 外接电视机或VGA显示器
方案:
输出接口: AV/VGA
视频播放: MPEG4: DIVX/AVI
MPEG2: MPG/VOB (DVD/SVCD)
MPEG1: MPG/DAT(VCD)
音频播放: MP3、WMA
图片浏览: JPEG
分辨率: >500TV Line
PC 连接: USB2.0
操作方式: 遥控器配合OSD菜单
视频制式: PAL/NTSC制式
电源要求: DC5.0V
尺寸: 131 (L) X80 (H) X 19 (D) mm
重量: 约215g
其它功能: 特有OTG一键拷贝按钮



HDS-01  
Without HDD

HDD: 2.5"(20G/30G/40G/60G/80G)
TV format: PAL/NTSC
Disk type: MPEG4/DVD/MP3/JPEG/VCD
Video SNR: $\geq 56$ dB
Frequency response: 20Hz-20KHz $\pm 1$ dB
Dynamic range: $\geq 90$ dB
S/N ratio: $\geq 90$ dB
D/A switch: 96KHz/24bit
Video output: 1Vp-p(75 $\Omega$ )
Audio output: 2.0+0.0V -1.0V
Power consumption: AC 100-240V 50/60Hz
Consume power: $\leq 5$ W
Dimension: 132 (L) X80 (H) X 19 (D) mm
Weight: Approx.215g

FOB SHENZHEN
USD 40/PC (Basis on 100pcs)
USD 38/pc (Basis on 500pcs)
USD 37/PC (Basis on 1K)
USD 42/PC (Sample Cost)



HDS-03  
Without HDD

HDD: 2.5 inch, (20G/40G/80G)	
Power Supply: DC 5.6V	
Power Consumption: $\leq 800\text{MA}$	USD 42/PC
Video system: AUTO / PAL / NTSC	(Basis on 100pcs)
Playable Programs: MPEG4, DVD, SVCD, JPEG, MP3, CD-DA	
Video Output: 1.0Vpp+/-0.1(75ohm)	USD 40/pc
Audio Output: 2.0Vrms+/-0.3V	(Basis on 500pcs)
Remote-control System: Infrared pulse, DC3V, Button Battery	
Features of Audio signal Output:	USD 38/PC
Frequency Response 20Hz---22kHz	(Basis on 1K)
S/N Ratio $\geq 90\text{dB}(1\text{kHz } 0\text{dB})$	
Dynamic Range $\geq 80\text{dB}(1\text{kHz } 0\text{dB})$	USD 45/PC
THD 0.04%	(Sample Cost)
Audio Distortion Lower than test level	
Crosstalk $\geq 80\text{dB}(1\text{kHz } 0\text{dB})$	
Dimension: 132 (L) X80 (H) X 19 (D) mm	
Weight: Approx.215g	

FOB SHENZHEN



HDS-05  
Without HDD

HDD: 2.5 inch, (20G/40G/80G)	
Power Supply: DC 5.6V	
Power Consumption: $\leq 800\text{MA}$	
Video system: AUTO / PAL / NTSC	
Playable Programs: MPEG4, DVD, SVCD, JPEG, MP3, CD-DA	
Video Output: 1.0Vpp+/-0.1(75ohm)	
Audio Output: 2.0Vrms+/-0.3V	
Remote-control System: Infrared pulse, DC3V, Button Battery	
Features of Audio signal Output:	
Frequency Response 20Hz---22kHz	
S/N Ratio $\geq 90\text{dB}(1\text{kHz } 0\text{dB})$	
Dynamic Range $\geq 80\text{dB}(1\text{kHz } 0\text{dB})$	
THD 0.04%	
Audio Distortion Lower than test level	
Crosstalk $\geq 80\text{dB}(1\text{kHz } 0\text{dB})$	
Dimension: 132 (L) X80 (H) X 19 (D) mm	
Weight: Approx.215g	

FOB SHENZHEN

USD 42/PC  
(Basis on 100pcs)

USD 40/pc  
(Basis on 500pcs)

USD 38/PC  
(Basis on 1K)

USD 45/PC  
(Sample Cost)